



GUJRAT NARMADA VALLEY FERTILIZERS AND CHEMICALS LIMITED

Regd. Office: PO: Narmadanagar-392015, Dist: Bharuch (Gujarat) INDIA

CIN: L24110GJ1976PLC002903

20th February,2020

Requirement of “BENZENE” for the production of ANILINE at GNFC BHARUCH plants.

GNFC intend to procure approximately **300 ~ 500 MT (±10%) of BENZENE during February'20 and 2,300 MT (±10%) of BENZENE during March'20 i.e total 2,600 ~ 2,800 MT (±10%) BENZENE** on FOR GNFC, Bharuch site basis as per the Technical Specifications mentioned hereunder at “Annexure-A”

ELIGIBILITY CRITERIA:

- ✓ The bidder must have an arrangement for sufficient storage of BENZENE in order to ensure supply of offered BENZENE quantity uninterruptedly during the Contract period.
- ✓ Bidder must have been engaged in the business of manufacturing/trading for the sale and supply of BENZENE for a minimum period of **03 (THREE)** years.
- ✓ Net Worth during the last audited financial years shall be positive.

Bidders who are interested to participate in the tender and having capacity to confirm above criteria are hereby intimated to contact following officials for further information to submit their offers.

Such interested bidders shall have to send their request mail for issue of Tender enquiry to the following officials on or before 22.02.2020 15.00 Hrs. IST.

Contact Persons:

- | | |
|---|---------------------------------|
| 1. VM Patel, Addl. General Manger | - Email ID : vmpatel@gnfc.in |
| 2. NB Desai, Chief Manager | - Email ID :nbdesai@gnfc.in |
| 3. SM Shah, Senior Manager | - Email ID : sureshshah@gnfc.in |
| 4. AA Thakkar, Senior Materials Officer | - Email ID : aathakkar@gnfc.in |

B S Limbachia
General Manager



GUJRAT NARMADA VALLEY FERTILIZERS AND CHEMICALS LIMITED

Regd. Office: PO: Narmadanagar-392015, Dist: Bharuch (Gujarat) INDIA

CIN: L24110GJ1976PLC002903

APPENDIX- A

DETAILED SPECIFICATIONS OF BENZENE

1) Benzene purity	:	99.95% by wt. Min. (Test Method- ASTM D-4492)
2) Appearance	:	Clear colorless liquid free from un-dissolved water at outdoor temperature and free from mechanical impurities (Test Method- Visual).
3) Solidification point	:	5.45 °C Minimum
4) Specified gravity @ 15.5 Deg C	:	0.882 to 0.886 gm/ml.
5) Toluene	:	0.025% w/w Max. (Test Method- ASTM D-4492)
6) Aliphatic Hydrocarbon	:	0.025% w/w Max. (Test Method- ASTM D-4492)
7) Moisture	:	300 PPM Max.
8) Total Sulphur/Thiophene	:	1 mg / kg Max. (Test Method- ASTM D-4492)
9) Distillation Range	:	< 0.6 Deg. C including 80.1 (1 to 96% volume)
10) Residue on Evaporation	:	10 mg/kg Max.
11) Color	:	10 APHA max.
12) Acid wash color	:	1 max.
13) Bromine Index	:	10 mg Br / 100gm.
14) Acidity	:	Nil /mg NaOH /100 gm.
