



GUJRAT NARMADA VALLEY FERTILIZERS AND CHEMICALS LIMITED

Regd. Office: PO: Narmadanagar-392015, Dist: Bharuch (Gujarat) INDIA

CIN: L24110GJ1976PLC002903

20th April'2019

Requirement of 1,000 MT (\pm 5%) of TOLUENE

GNFC intend to procure approximately 1,000 (\pm 5%) MT of TOLUENE on FOR GNFC, Bharuch site basis/ CFR WCI Sea Port,India as per the Technical Specifications mentioned hereunder at "Annexure-A"

ELIGIBILITY CRITERIA:

- a) Bidder must have been engaged in the business of manufacturing/trading for the sale and supply of TOLUENE for a minimum period of 02 (TWO) years.
- b) The bidder must have an arrangement for sufficient storage of TOLUENE in order to ensure supply of offered quantity uninterruptedly during the Contract period.
- c) Net Worth during the last audited financial years shall be positive.

The bidders who are interested to participate in the tender meeting above eligibility criteria are hereby intimated to contact following officials for further information to submit their offers.

Such interested bidders shall have to send their request mail for issue of Tender enquiry to the following officials on or before **29.04.2019, 14.00 Hrs. IST**.

Contact Persons:

- | | |
|-----------------------------------|----------------------------------|
| 1. BS Limbachia, General Manger | - Email ID : bslimbachia@gnfc.in |
| 2. VM Patel, Addl. General Manger | - Email ID : vmpatel@gnfc.in |
| 3. S M Shah, Sr. Manager | - Email ID : sureshshah@gnfc.in |

**B S Limbachia
General Manager (MM)**



GUJRAT NARMADA VALLEY FERTILIZERS AND CHEMICALS LIMITED

Regd. Office: PO: Narmadanagar-392015, Dist: Bharuch (Gujarat) INDIA

CIN: L24110GJ1976PLC002903

ANNEXURE-A

TECHNICAL SPECIFICATIONS OF TOLUENE

- | | |
|---|--|
| 1) Appearance | : Clear colour less liquid free from undissolved water at outdoor temperature and free from mechanical impurities.(Test Method:Visual) |
| 2) Specific Gravity | : 0.865 to 0.874 at 15.5 °C (Test Method: ASTM D 4052) |
| 3) Toluene% w/w | : 99.8 Minimum (Test Method: ASTM D 2360) |
| 4) Benzene% w/w | : 0.05 Maximum(Test Method: ASTM D 2360) |
| 5) Aliphatic Hydrocarbon % w/w | : 0.1 Maximum (Test Method: ASTM D 2360) |
| 6) Xylene & Ethylbenzene % w/w | : 0.03 Maximum (Test Method: ASTM D 2360) |
| 7) Total Other Aromatic Hydrocarbon % w/w | : 0.02 Maximum (Test Method:ASTM D 2360) |
| 8) Total Sulphur / Thiophene mg/kg | :1 Maximum (Test Method: ASTM D 4735 For Thiophene) |
| 9) Colour after acid wash | : No darker than NO-2 according to colour code (Test Method: ASTM D 848) |
| 10) Copper Corrosion | :copper tin must not show rainbow gloss nor a grey or black deposit or discoloration (Test Method: ASTM D 849) |
| 11) Neutralization test | : Passes (Test Method: ASTM D 847) |
